LABDEX

Blood Bank Refrigerator LX4004BBR

Email: info@labdex.com **website:** www.labdex.com

Description

Blood Bank Refrigerator LX4004BBR is an upright type made up of color sprayed steel (outside) and stainless steel material (inside). It is designed by keeping in mind strict requirements for storage of blood and blood components. It is a microprocessor-based temperature controller with digital display allows user to maintain temperature up to 4 ±1 °C.

Specifications

Capacity	1008 L
Bloodbags (450ml)	576
Shelf/drawer	Shelves/12
Cooling method	Forced air cooling
Defrost	Auto
Refrigerant	R134a
Noise	53 (db)
Ambient temperature	10~32 ℃
Temperature range	4±1 ℃
Compressor	SECOP/1
Sensor type	NTC
Temperature controller	Microprocessor
Display	Digital display
Inside material	Stainless steel
Outside material	Color sprayed steel
Insulation	PURF
Power consumption	8.53 (kWh/24h)
Power	513 W
Current	2.37A

Voltage/Frequency	220V/50Hz
Interior size (W x D x H)	1100 x 684 x 1325 mm
Exterior size (W x D x H)	1240 x 860 x 1895 mm
Package size (W x D x H)	1330 x 970 x 2130 mm
Net weight	270 kgs
Gross weight	340 kgs

Features

- Designed with individual transparent inner door
- Micro-processor controlled function with digital display
- Designed with forced air cooling system
- It has twelves shelves with shelves height adjustable function
- 3 standard locks with keys for 3 doors
- LED interior light
- It has various type of alarm function such as High/low temperature, Power failure, Thermostat failure, Power failure backup system and Door ajar
- Auto defrost function
- CFC-free refrigerant and energy-saving
- Equipped with Thermal Printer

Applications

- Used to store blood, research laboratories, clinical research laboratories and in pathological testing.

Standard Accessories

- Caster
- Test hole

Optional Accessories

- Chart recorder

71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.
Email: info@labdex.com | Website: www.labdex.com